


GOAL
SINGLE CYLINDER
GK725 0 - GK625 0 - GK525 0



SINGLE CYLINDER

GK725 0 - GK625 0 - GK525 0




KNITTING HEAD
designed to knit high quality items and ensure constant reliability over time.

SINKERS CAP
high speed for higher production

NEW ELECTRONICS
with high resolution touch screen display

NEW BASE
designed to increase solidity and rigidity, allows a more ergonomic assembling of components



All images in this brochure are indicative and not binding.

SINGLE CYLINDER GK725 0 - GK625 0 - GK525 0

Goal Series 2 feeds machines are designed to offer maximum productivity. They are available in different diameters with different numbers of needles. Latest generation electronics provides control and execution of all machine commands. Drawings and articles are created and managed by Digraph 3 Plus software package, which contains a full collection of styles the operator can combine in different ways to obtain the desired results.

- 5 colors pattern on single feed course, plain knit
- Reciprocated heel and toe in different sizes, 3D effects
- 28 yarn fingers
- Rising dial and finger plate with stepping motor
- 9 electronic actuators for needle selection
- Brushless coaxial main motor

MACHINE DIMENSIONS



Lenght max cm 94.5
Depth max cm 103.7
Height max cm 180

MACHINE WEIGHT



ca. 230 Kg

SINGLE CYLINDER

GK725 0 - GK625 0 - GK525 0

TECHNICAL DATA

MODEL	CYLINDER DIAMETER	GAUGE	NEEDLE THICKNESS
GK725 0	3"1/2	7 1/2 to 20	0.85 - 0.70 - 0.60 mm
GK625 0	3"3/4	from 7 to 20	0.85 - 0.70 - 0.60 mm
GK525 0	4"	from 6 1/2 to 20	0.85 - 0.70 - 0.60 mm

Above data are indicative and not binding.

STANDARD DEVICES

- Stepper motor electric dial with adjustable height
- Stitch cam feeds 1 and 2 with 2 different heights.
- High speed sinker cap
- High resolution touch screen display
- Yarn sliding sensors guard cleaning device
- Heel yarn recover device with four positions
- 14 color yarn fingers
- 9 yarn fingers on first feed, 6 on second feed
- Yarn creel
- USB port
- Circular yarn cutter with mechanical stop
- 1 yarn finger on inlaid elastic feed
- Stepper motor controlled adjustable suction valve

MAIN OPTIONAL DEVICES

- LGL Eco Power or Eco Compact yarn storage feeder
- Dinema YoYo positive yarn feeders
- Elastic yarn positive feeders, for compression socks
- Dinema Plus elastan positive feeders
- Stitch cam on first and second feed, 3 heights
- Motorized stitch cams
- Motorized sinkers cap for sinkers pressure
- Motorized sinkers cap for sinker pressure and angular position
- Antitwist device
- Footlet device
- Elastane extra pliers device
- Recover yarn device, 6 positions
- Yarn trimming circular cutter with adjustable speed
- Preparation for storage feeder "Unifeeder 2" by BTR
- Ethernet board for connection to Dinema Nautilus data collector system
- Second elastic yarn finger, on second feed
- Yarn sliding control sensors, Dinema ISPY
- Pneumatic yarn tensioner for covered elastane
- Suction fan

POSSIBLE KNITTING

The standard machine can perform the following knittings

- Mesh, tuck and float stitch, jacquard, 2 feeds
- 5 colors pattern plus ground color, mesh, tuck and float stitch, 1 feed
- With laid-in elastic: 5 colors pattern plus ground color, tuck and float stitch, 1 feed
- With laid-in elastic: mesh, tuck and float stitch, 4 colors pattern plus ground
- Laid-in elastic on 2 feeds, that is one course elastic every two knitted course
- With the second elastic yarn finger 4 colors pattern on course plus ground, tuck and float stitch, one feed
- With the second elastic yarn finger 3 colors pattern on course plus ground, mesh, tuck and float stitch, one feed

SINGLE CYLINDER

GK725 0 - GK625 0 - GK525 0

NUMBER OF COLORS

Number of colors	5 colors on course plus ground color, one feed
------------------	--

PERFORMANCES

	3" 1/2 3" 3/4 4" CYLINDERS
KNITTING FEATURES	Patterns or selections 300rpm Plain knit without pattern 350rpm
MAXIMUM SPEED	350 rpm

Above data are indicative and not binding.

DISCLAIMER: maximum speed may vary depending on yarn, knitting, lubrication etc

GAUGE

Model	ø	GAUGE																											
		6½	7	7½	8	8½	9	9½	10	10½	11	11½	12	12½	13	13½	14	14½	15	15½	16	16½	17	17½	18	18½	19	20	
GK525 0	4"	84	88	96		108	112	116	120	128	132	136	144		156	160	168	176	180	188	192	200		216	220			240	256
		Needle thickness 0.85 mm												Needle thickness 0.70 mm						Needle thickness 0.60 mm									
		Needle thickness 0.70 mm						Needle thickness 0.70 mm						Needle thickness 0.60 mm															
GK625 0	3"3/4	84	88	96		108	112	116	120	128	132		144		156	160	168		176	180	188	192	200			216	220		240
		Needle thickness 0.85 mm												Needle thickness 0.70 mm						Needle thickness 0.60 mm									
		Needle thickness 0.70 mm												Needle thickness 0.70 mm						Needle thickness 0.60 mm									
GK725 0	3"1/2			84	88	96	100		108	112	116	120	128	132		144		156		168			180		192	200			220
		Needle thickness 0.85 mm												Needle thickness 0.70 mm						Needle thickness 0.60 mm									
		Needle thickness 0.70 mm												Needle thickness 0.70 mm						Needle thickness 0.60 mm									

Above data are indicative and not binding.

DISCLAIMER:

All features in the brochure are for information only and subject to change without any prior notice.

For a complete list of available options, please contact Lonati sales network. The Company accepts no liability for improper use of machinery.

SINGLE CYLINDER

GK725 0 - GK625 0 - GK525 0

ELECTRIC POWER CONSUMPTION

With program for medium length socks.

MACHINE MODEL	CONSUMPTION kWh
GK725 0 - GK625 0 - GK525 0	0.45 – 0.50

COMPRESSED AIR CONSUMPTION

Gauge pressure 6,5 bar humidity 0% and dryer outlet temperature 18°C-21°C.

MACHINE MODEL	CYCLE TIME	CONSUMPTION FOR SOCK	CONSUMPTION PER MINUTE
GK725 0 - GK625 0 - GK525 0	2'45"	NI 11 - ft ³ 0.388	NI 4 - Cfm 0.141

SUCTION CONSUMPTION

Cylinder suction value = 850 mm/H2O - Holding yarns nozzle suction value = 850mm/H2O - Average consumption = 2.5 m³/min.

NOISE LEVEL (Maximum noise output for GK series models)


Noise pressure level on reference surface = LPA 79,5 dB - Noise power level = LWA 96,6 dB - Peak= 109,3 dB

LUBRICANTS


Average consumption for 100 dozens= 270 gr. Lonati recommends: Kluber Madol 183 Supreme - Fuchs Trax 16C

GREASE


For seals, bearings etc: Lonati recommends:TechnolubeSeals Damping grease Nyogel 774F-1




DESCRIPTION	CODE	NR. OF REELS	WEIGHT KG.	NOTES
Yarn creel	G1930040	28	20	Standard version
Yarn creel	G1930041	28	20	Version with BTR sensors



DESCRIPTION	CODE	NR. OF REELS	WEIGHT KG.	NOTES
Yarn creel	G1930040	28	20	Standard version
Yarn creel	G1930041	28	20	Version with BTSR sensors



DESCRIPTION	CODE	NR. OF REELS	WEIGHT KG.	NOTES
Yarn creel	G3930061	28	51	Standard version
Yarn creel	G3930062	28	51	Version with BTSR sensors



DESCRIPTION	CODE	NR. OF REELS	WEIGHT KG.	NOTES
Yarn creel	G3930061	28	51	Standard version
Yarn creel	G3930062	28	51	Version with BTSR sensors

NOTE

GK725 0 - GK625 0 - GK525 0





LONATI SPA

Via Francesco Lonati, 3 | 25124 Brescia (Italy)
Tel. +39 030 23901 | Fax +39 030 2310024
C.F.: 01469680175 | P.iva: 02096730961
info@lonati.com - www.lonati.com